

# ZOOMLION

## TELESCOPIC BOOM LIFTS

### ZT23J/ZT26J

Comply with CE/ANSI/CSA Standard



### HIGHLIGHTS

- ▶ Parallel four-link lifting mechanism for smooth boom movement
- ▶ Hexagonal boom design with good anti-fatigue performance and strong rigidity
- ▶ Smooth leveling and flexible chassis steering
- ▶ Load sensitive system, saving energy
- ▶ Upgraded telematics for high efficient service
- ▶ Deadweight lowering system for smooth operation and energy efficiency

### FEATURES

#### Standard Features

|                            |
|----------------------------|
| Horn                       |
| Proportional control       |
| Motion alarm               |
| Flashing beacon            |
| Self-closing entry gate    |
| Emergency descent system   |
| Emergency stop button      |
| Auto-leveling system       |
| On-board diagnostic system |
| Tilt protection system     |
| Oscillating axle           |
| Load sensing system        |
| 4.3' Led display           |
| Swing-out engine tray      |

#### Accessories & Options

- ▶ Platform work light
- ▶ Anti-collision device
- ▶ AC power to platform





## ACCESS WITH ZOOMLION GREEN

Phone: 0086(731)-88353692  
E-mail: awp@zoomlion.com


Add: 701 Xulong Nan Lu, Xiangjiang New District, Changsha Hunan, China  
Web: www.zoomlion-access.com

### ZOOMLION

| Model                                       | ZT23J                                                                                                            |           | ZT26J                                                                                                        |           |
|---------------------------------------------|------------------------------------------------------------------------------------------------------------------|-----------|--------------------------------------------------------------------------------------------------------------|-----------|
|                                             | Imperial                                                                                                         | Metric    | Imperial                                                                                                     | Metric    |
| Size                                        |                                                                                                                  |           |                                                                                                              |           |
| Work Height                                 | 82ft 4in                                                                                                         | 25.1 m    | 94ft 1in                                                                                                     | 28.7m     |
| Platform Height                             | 75ft 9in                                                                                                         | 23.1 m    | 87ft 7in                                                                                                     | 26.7m     |
| Horizontal Outreach                         | 59ft 4in                                                                                                         | 18.1m     | 72ft 6in                                                                                                     | 22.1m     |
| A - Stowed Length                           | 34ft 5in                                                                                                         | 10.5 m    | 39ft                                                                                                         | 11.91m    |
| B - Stowed Width                            | 8ft                                                                                                              | 2.45m     | 8ft 2in                                                                                                      | 2.49m     |
| C - Stowed Height                           | 9ft                                                                                                              | 2.75m     | 9ft 3in                                                                                                      | 2.82m     |
| D - Platform Length                         | 8ft                                                                                                              | 2.44m     | 8ft                                                                                                          | 2.44m     |
| E - Platform Width                          | 3ft                                                                                                              | 0.91m     | 3ft                                                                                                          | 0.91m     |
| F - Wheelbase                               | 8ft 3in                                                                                                          | 2.52m     | 9ft 2in                                                                                                      | 2.8m      |
| Tread                                       | 8ft                                                                                                              | 2.45m     | 8ft 2in                                                                                                      | 2.49m     |
| G - Ground Clearance                        | 1ft 3in                                                                                                          | 0.4m      | 1ft 3in                                                                                                      | 0.4m      |
| H - Transport length                        | 31ft 17in                                                                                                        | 9.5m      | 31ft 17in                                                                                                    | 9.5m      |
| I-Transport height                          | 10ft 17in                                                                                                        | 3.1m      | 10ft 17in                                                                                                    | 3.1m      |
| Performance                                 |                                                                                                                  |           |                                                                                                              |           |
| Platform Capacity (Unrestricted/Restricted) | 660/1000lb                                                                                                       | 300/454kg | 660/1000lb                                                                                                   | 300/454kg |
| Drive Speed (Stowed)                        | 3.73mph                                                                                                          | 6.0km/h   | 3.42mph                                                                                                      | 5.5km/h   |
| Gradeability                                | 45% (24°)                                                                                                        | 45% (24°) | 45% (24°)                                                                                                    | 45% (24°) |
| Turning Radius (Inside)                     | 7ft 10in                                                                                                         | 2.4m      | 11ft 5in                                                                                                     | 3.5m      |
| Turning Radius (Outside)                    | 17ft 9in                                                                                                         | 5.4m      | 20ft                                                                                                         | 6.1m      |
| Turntable Swing                             | 360° continuous                                                                                                  |           | 360° continuous                                                                                              |           |
| Platform Rotation                           | ±90°                                                                                                             |           | ±90°                                                                                                         |           |
| Tail Swing                                  | 5ft 4in                                                                                                          | 1.65m     | 5ft 8in                                                                                                      | 1.75m     |
| Jib (Range of Articulation)                 | 130° (-55°~75°)                                                                                                  |           | 130° (-55°~75°)                                                                                              |           |
| Max. Wind Speed                             | 28mph                                                                                                            | 12.5m/s   | 28mph                                                                                                        | 12.5m/s   |
| Power                                       |                                                                                                                  |           |                                                                                                              |           |
| Engine                                      | KUBOTA V2403(Stage V)<br>KUBOTA V2403 (Stage III)                                                                |           | KUBOTA V2607(Stage V)<br>KUBOTA V3307(Stage III)                                                             |           |
| Fuel Tank Capacity                          | 39.6 (us gal)                                                                                                    | 150L      | 39.6 (us gal)                                                                                                | 150L      |
| Control Voltage                             | 12V DC                                                                                                           |           | 12V DC                                                                                                       |           |
| Hydraulic Tank Capacity                     | 39.6 (us gal)                                                                                                    | 150L      | 39.6 (us gal)                                                                                                | 150L      |
| Drive Mode                                  | 4WD                                                                                                              |           | 4WD                                                                                                          |           |
| Steering Mode                               | Front-wheel                                                                                                      |           | Front-wheel                                                                                                  |           |
| Tire                                        |                                                                                                                  |           |                                                                                                              |           |
| Type                                        | 36×14-20 solid tire (standard)<br>355/55-24.5 foam-filled tire (option)<br>355/55D-625 foam-filled tire (option) |           | 385/65-24 solid tire (standard)<br>15-625 foam-filled tire (option)<br>385/55-24.5 foam-filled tire (option) |           |
| Weight                                      |                                                                                                                  |           |                                                                                                              |           |
| Gross                                       | 27557lb                                                                                                          | 12500kg   | 38360lb                                                                                                      | 17400kg   |



Range of Motion ZT23J



Range of Motion ZT26J

ZOOMLION ACCESS reserves the right to make specification and/or equipment changes without prior notification.  
Product specifications are updated to May, 2026.